



LUMBER LOCK

HEAVY DUTY SUBFLOOR ADHESIVE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION:

Miracle® Lumber Lock is a heavy-duty adhesive, which provides a durable weatherproof and permanent bond that is stronger than the lumber it locks together. **Lumber Lock®** conforms to HUD UM 60A and exceeds performance requirements of ASTM D3498 for Field-Gluing Plywood to Wood Framing. **Lumber Lock®** provides quick tack and a permanently flexible bond when applied to wet, frozen and chemically pressure-treated or untreated lumber, and many other substrates.

ADVANTAGE:

- Quick Tack
- High Strength bonds
- Permanently Flexible
- Absorbs Vibrations
- Reduces Nail Pops
- Superior Aging Characteristics
- Bridges Framing Irregularities
- Resists Impact and Deflection
- All-Weather Versatility
- Greater Structural Floor Systems Strength
- Reduces Squeaks and Bounce
- Passes ASTM D3498

TYPICAL USES:

LUMBER LOCK is most recognized as a subfloor adhesive, but is extremely versatile and can be used in a variety of wood construction projects, including:

- Stairs, Stair Treads, Risers and Stringers
- Underlayment to Joists
- Tongue & Groove Boards
- Paneling
- Sheet & Lap Siding to Studs
- Porches & Patios
- Decks & Docks
- Fences & Ramps

TYPICAL PROPERTIES:

Property	Typical Value
Base:	Synthetic Polymer
Solvent:	Organic Solvent
Shelf Life:	1 year from Date of Manufacture*
Colors:	Tan
Flash Point:	-9.4 F (-23 C)
Weight/ Gallon	8.86 lbs/ gallon
VOC Content	420.5 g/L (EPA Method 24)
Viscosity	275,000 – 312,500 cps
Open Time	15 minutes
Dry Time	48 – 72 hours
Solids	62.2% ± 3.0%
Coverage	38 linear feet using 3/8" bead
Formaldehyde	No urea formaldehyde added during adhesive manufacturing

* The shelf life for an unopened container of this adhesive stored at temperatures between 60°F (15.6°C) and 95°F (35°C) is 1 year from date of manufacture. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing container directly on the floor or against an outside wall

DIRECTIONS FOR USE:

- Use only after careful consideration of the warnings, directions, and first aid instructions given. Do not thin.

SURFACE PREPARATION

- Precut lumber to size.
- Prepare all other installation materials before applying adhesive.
- For best results, remove free standing ice, snow, water, mud, sawdust and other foreign material which will impair adhesion.

APPLICATION

- Cut nozzle tip on a slant to provide a 3/8" bead and puncture the inner seal at the base of the spout.
- Apply a continuous bead of adhesive to one surface to be bonded. Where panel ends butt on a joist, apply a zig-zag bead of adhesive under each panel. Spread into groove of panels.
- For subfloor, deck and dock applications, allow 1/8" spacing for expansion at ends and edges of panels, and fasten plywood at all supports with galvanized finishing nails.
- Press surfaces firmly together with slight twisting motion. Bonding should be made within 15 minutes of adhesive application.
- Allow 24 – 48 hours before submitting application to heavy traffic.

- Maximum bond strength will be achieved in approximately 28 days.
- Do not use on rigid plastics, polystyrene foam or tub kits.

ATTENTION:

- Empty container remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists.
- Do not reuse empty container. Dispose of, according to all federal, state, and local regulations.

**KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL OR INDUSTRIAL USE ONLY
USE ONLY WITH APPROVED EQUIPMENT**

NOTICE TO PURCHASER:

NO WARRANTIES, EXPRESS OR IMPLIED, ARE MADE INCLUDING MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. EXCEPT FOR PERSONAL INJURY RESULTING FROM USE OF THE PRODUCT AS DIRECTED, ITW POLYMERS SEALANTS NORTH AMERICA, INC. SHALL NOT BE LIABLE IN TORT OR CONTRACT FOR ANY LOSS OR DAMAGE. UNDER NO CIRCUMSTANCES SHALL ITW POLYMERS SEALANTS NORTH AMERICA, INC., A DIVISION OF ILLINOIS TOOL WORKS INC., OR ITS AFFILIATES ("ITW POLYMERS SEALANTS NORTH AMERICA, INC.") BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES. THE USER MAY SEND A SAMPLE OF PRODUCT TO ITW POLYMERS SEALANTS NORTH AMERICA, INC. FOR TESTING. IF SUCH TESTING PROVES A PRODUCT DEFECTIVE, THE USER'S SOLE AND EXCLUSIVE REMEDY IS EITHER REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT OR REPLACEMENT OF THE CONTAINER OF PRODUCT. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF ITW POLYMERS SEALANTS NORTH AMERICA, INC. HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATIONS OF THIS.

WARRANTY:

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH VARY FROM STATE TO STATE; THEREFORE, SOME OF THE LIMITATIONS STATED ABOVE MAY NOT APPLY TO YOU. IT IS TO YOUR BENEFIT TO SAVE YOUR DOCUMENTATION UPON PURCHASE OF A PRODUCT. THE INFORMATION AND SUGGESTIONS FOR USE CONTAINED HEREIN ARE BELIEVED TO BE ACCURATE, BUT ARE NOT TO BE CONSTRUED AS WARRANTIES. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS OR HER INTENDED USE AND SHALL ASSUME ALL RISK ASSOCIATED THEREWITH.

Complete technical information is available from
ITW Polymers Sealants North America, Inc.