

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: MIRACLE DSA 40 Drywall and Foamboard Adhesive

MANUFACTURER

ITW Polymers Sealants North America
 56 Air Station Industrial Park
 Rockland, MA 02370

Product Stewardship: (781) 878-7015

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

COMMENTS: MIRACLE is a registered trademark of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Aspiration Hazard, Category 1
 Skin Irritation, Category 3
 Eye Irritation, Category 4
 Target Organ Toxicity (Repeated exposure), Category 2

GHS LABEL



Health
hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H304: May be fatal if swallowed and enters airways.
 H331: Toxic if inhaled.
 H315 + H320: Causes skin and eye irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENT(S)

Prevention:

P102: Keep out of reach of children.
 P103: Read label before use.
 P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P264: Wash thoroughly after handling.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P307+P311: IF exposed: Call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P391: Collect spillage.

P362+P364: Take off contaminated clothing and wash it before reuse.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! Contains crystalline silica (quartz). Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis may be progressive; it may lead to disability and death. Crystalline silica (quartz) inhaled from occupational sources is classified as carcinogenic to humans.

POTENTIAL HEALTH EFFECTS

EYES: Mildly irritating to the eyes.

SKIN: Not likely to be absorbed in toxic amounts. Prolonged exposure may cause skin irritation. Avoid skin contact as much as possible.

SKIN ABSORPTION: None Expected.

INGESTION: This material may be harmful or fatal if swallowed in large quantities. Small amounts are not expected to produce adverse health effects.

INHALATION: Slight irritation to nose and throat with prolonged or repeated exposure.

CARCINOGENICITY: IARC has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group I)."

ROUTES OF ENTRY: Eye and skin contact. Inhalation and ingestion are unlikely routes of entry.

IRRITANCY: Slight eye and skin irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
VM&P Naphtha	3 - 10	8032-32-4
Methanol	1 - 5	67-56-1
Silica, Crystalline	< 0.5	14808-60-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Small amounts are not expected to produce adverse health effects. Larger amounts should be recovered by aspiration. Get medical attention.

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

INHALATION: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough or other symptoms develop.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Slight irritation.

SKIN: Slight skin irritation.

SKIN ABSORPTION: None Expected.

INGESTION: None known, not likely route of entry.

INHALATION: Materials are low in volatility therefore not likely to pose a problem.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class IIIB

GENERAL HAZARD: Combustible Liquid.

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon Monoxide, Carbon Dioxide

EXPLOSION HAZARDS: Decomposition products may cause a health hazard.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear. After water evaporates, remaining material will burn.

SENSITIVE TO STATIC DISCHARGE: Not Applicable

SENSITIVITY TO IMPACT: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes, smoke, carbon monoxide and carbon dioxide may form when heated to decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation).

HANDLING: Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Follow all SDS/label precautions even after container is emptied because they may retain product residues.

STORAGE: Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: 1 year from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
VM&P Naphtha	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	300 ppm	1370 mg/m ³
		STEL	NL [1]	NL [1]
Methanol	OSHA PEL	TWA	200 ppm	260 mg/m ³
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	200 ppm	262 mg/m ³
		STEL	250 ppm	327 mg/m ³
Silica, Crystalline	OSHA PEL	TWA	NL	0.1 mg/m ³
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL	0.05 mg/m ³
		STEL	NL [1]	NL [1]

Footnotes:
1. NL = Not Listed

ENGINEERING CONTROLS: Natural ventilation should be adequate under normal conditions.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields. A face shield may be necessary if spraying the product.

SKIN: Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

RESPIRATORY: No respiratory protection required under normal conditions.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

SAFETY DATA SHEET

Date Prepared : 11/28/2017

MSDS No : 2108

Date Revised : 11/28/2017

Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid**ODOR:** Latex**ODOR THRESHOLD:** Not Determined**COLOR:** Tan**pH:** Not Determined**PERCENT VOLATILE:** 35.4**Notes:** by weight**FLASHPOINT AND METHOD:** Not Applicable**FLAMMABLE LIMITS:** Not Applicable**AUTOIGNITION TEMPERATURE:** Not Applicable**VAPOR PRESSURE:** Not Determined**VAPOR DENSITY:** Not Determined**BOILING POINT:** $\geq 100^{\circ}\text{C}$ (212 $^{\circ}\text{F}$)**FREEZING POINT:** Not Determined**MELTING POINT:** Not Determined**POUR POINT:** Not Determined**SOLUBILITY IN WATER:** Soluble**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined**EVAPORATION RATE:** < 1.0 (n-Butyl Acetate=1)**DENSITY:** 9.92 lbs/gal**PARTICLE SIZE:** Not Determined**SPECIFIC GRAVITY:** 1.19**VISCOSITY:** Not Determined**MOLECULAR WEIGHT:** Not Determined**(VOC):** 182.4 gr/L EPA Method 24 VOC**Notes:** Photochemically Reactive Only VOC: 129.0 gr/L**OXIDIZING PROPERTIES:** Not Determined**COMMENTS:** 0.06 lb VHAP/lb Solid
3.6% by weight HAP

10. STABILITY AND REACTIVITY

REACTIVITY: Yes**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.**STABILITY:** Stable.**CONDITIONS TO AVOID:** None known.**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and carbon dioxide may form when heated to

SAFETY DATA SHEET

Date Prepared : 11/28/2017
 MSDS No : 2108
 Date Revised : 11/28/2017
 Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

decomposition.

INCOMPATIBLE MATERIALS: Strong acids or alkaline materials.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
VM&P Naphtha	> 8000 mg/kg	> 4000 No data	3400 ppm (4-hr dose)
Methanol	No data	12800 mg/kg (rabbits)	64000 ppm (4-hr dose - rat)
Silica, Crystalline	No data	No data	No data

SERIOUS EYE DAMAGE/IRRITATION: Slight eyes and skin irritation.

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status
Silica, Crystalline	1	1

IARC: IARC has concluded that "crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group I)."

NOTES: This product contains silica quartz, a chemical known to the State of California to cause cancer.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated

MARINE POLLUTANT #1: None

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** No **CHRONIC:** No

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Methanol	1 - 5	67-56-1

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Methanol	1 - 5	5,000 lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
VM&P Naphtha	8032-32-4
Methanol	67-56-1
Silica, Crystalline	14808-60-7

CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Methanol	1 - 5	67-56-1

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Methanol	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical
Silica, Crystalline	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

CALIFORNIA PROPOSITION 65: This product contains silica, quartz, a chemical known to the state of California to cause cancer.

Chemical Name	Wt.%	Listed
Silica, Crystalline	< 0.5	Cancer

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic

16. OTHER INFORMATION

Date Revised: 11/28/2017

SAFETY DATA SHEET

Date Prepared : 11/28/2017
MSDS No : 2108
Date Revised : 11/28/2017
Revision No : 7

MIRACLE DSA 40 Drywall and Foamboard Adhesive


INFORMATION CONTACT: (781) 878-7015

REVISION SUMMARY: This MSDS replaces the 10/04/2016 MSDS. Revised: **Section 1:** Date Issued.

HMIS RATING

HEALTH		1
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION	B	

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children
 For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.